

Wall Mounted 50-60Hz

Wall Mounted



Model			AP.UNAX028BC	AP.UNAX036BC	AP.UNAX040BC	AP.UNAX056BC	AP.UNAX063BC	AP.UNAX071BC
Capacity	Cooling	kW	2.8	3.6	4.0	5.6	6.3	7.1
	Heating	kW	3.0	4.3	4.5	6.0	7.1	8.0
Power supply		V/Ph/Hz	220V/1Ph/50Hz	220V/1Ph/50Hz	220V/1Ph/50Hz	220V/1Ph/50Hz	220V/1Ph/50Hz	220V/1Ph/50Hz
Power Input		W	65	65	70	70	82	82
Air flow volume(H/M/L)		m ³ /h	800/700/600	800/700/600	850/750/650	850/750/650	1200/950/860	1200/950/860
Sound pressure level(H/M/L)		dB(A)	40/36/32	40/36/32	45/41/35	45/41/35	48/45/38	48/45/38
Fan Fan motor	Type	-	Cross-flow fan	Cross-flow fan	Cross-flow fan	Cross-flow fan	Cross-flow fan	Cross-flow fan
	Quantity	-	1	1	1	1	1	1
	Speed (H/M/L)	rpm	1100/1000/900	1100/1000/900	1100/1000/900	1100/1000/900	1100/1000/900	1100/1000/900
	Power Input	W	30	30	30	30	50	50
Connecting pipe	Insulation class	-	B	B	B	B	B	B
	Liquid Pipe	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35
	Gas Pipe	mm	φ12.70	φ12.70	φ12.70	φ12.70	φ15.88	φ15.88
Drain pipe	Connection method		Flared	Flared	Flared	Flared	Flared	Flared
	External dia.	mm	DN20	DN20	DN20	DN20	DN20	DN20
Outline dimension		mm	970x315x235	970x315x235	970x315x235	970x315x235	1100x330x235	1100x330x235
Package dimension		mm	1010x370x300	1010x370x300	1010x370x300	1010x370x300	1140x385x300	1140x385x300
Net Weight		kg	13.5	13.5	14.5	14.5	16	16
Gross weight		kg	17.5	17.5	18.5	18.5	20	20

- Notes
1. Power supply: 220V/1PH for 50Hz
 2. The cooling condition: indoor side 27°C (80.6°F) DB, 19°C (60°F) WB outdoor side 35°C (95°F) DB
 3. The heating condition: indoor side 20°C (68°F) DB, 15°C (44.8°F) WB outdoor side 7°C (42.8°F) DB
 4. Sound level: measured at point 1m in front of the unit at a height of 1.3m. During actual operation, these values are normally somewhat higher as a result of ambient conditions.
 5. The above data may be changed without notice for future improvement on quality and performance.